

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2010

Revision: 30.05.2010

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**

- **Trade name:** Under Coat Omega100

- **Application of the substance / the preparation**

This Product Is designed for vehicle re finishing by professional painters only, in accordance with the manufactures instructions specified in the technical data sheet.

- **Manufacturer/Supplier:**

Kapci Coatings
Industrial Zone El - Raswa
Port Said
EGYPT
mohamed.rashad@kapci.com

- **Further information obtainable from:** Product safety department

- **Information in case of emergency:** During normal opening times: +20 66 3770000

2 Hazards identification

- **Hazard description:**



Xn Harmful

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 10 Flammable.

R 20/21 Harmful by inhalation and in contact with skin.

R 38 Irritating to skin.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **GHS label elements**



Warning

H226 - Flammable liquid and vapour.



Warning

H361d - Suspected of damaging the unborn child.



Warning

H332 - Harmful if inhaled.

H315 - Causes skin irritation.

- **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

- **Response:**

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P321 Specific treatment (see on this label).

- **Storage:**

P405 Store locked up.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2010

Revision: 30.05.2010

Trade name: Under Coat Omega100

(Contd. of page 1)

- **Disposal:**
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7	xylene Xn, Xi; R 10-20/21-38 Warning: 2.6/3; 3.1.D/4, 3.1.I/4, 3.2/2	10-25%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R 10-66-67 Warning: 2.6/3; 3.8/3	2.5-10%
CAS: 108-88-3 EINECS: 203-625-9	toluene Repr. Cat. 3; Xn, Xi, F; R 11-38-48/20-63-65-67 Danger: 2.6/2; 3.10/1, 3.7/2, 3.9/2 Warning: 3.2/2, 3.8/3	1-5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

GB

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2010

Revision: 30.05.2010

Trade name: Under Coat Omega100

(Contd. of page 2)

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

108-88-3 toluene

WEL	Short-term value: 384 mg/m ³ , 100 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk
-----	--

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2010

Revision: 30.05.2010

Trade name: Under Coat Omega100

(Contd. of page 3)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 124°C

· **Flash point:** 27°C

· **Ignition temperature:** 370°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 1.1 Vol %

Upper: 7.5 Vol %

· **Vapour pressure at 20°C:** 10.7 hPa

· **Density:** 1.47-1.52 g/cm³

· **Solubility in / Miscibility with**

water: Not miscible or difficult to mix.

· **Solvent content:**

Organic solvents: 38.0 %

VOC (EC) 38.00 %

Solids content: 62.0 %

10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Materials to be avoided:**

· **Dangerous reactions** No dangerous reactions known.

· **Dangerous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 30.05.2010

Revision: 30.05.2010

Trade name: Under Coat Omega100

(Contd. of page 4)

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

12 Ecological information

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Product:**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 Flammable liquids.

- **Danger code (Kemler):** 30

- **UN-Number:** 1993

- **Packaging group:** III

- **Hazard label:** 3

- **Description of goods:** 1993 FLAMMABLE LIQUID, N.O.S. (XYLENES, TOLUENE)

(Contd. on page 6)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 30.05.2010

Revision: 30.05.2010

Trade name: Under Coat Omega100

(Contd. of page 5)

· **Tunnel restriction code D/E**· **Maritime transport IMDG:**

- **IMDG Class:** 3
- **UN Number:** 1993
- **Label** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** FLAMMABLE LIQUID, N.O.S. (XYLENES, TOLUENE)

· **Air transport ICAO-TI and IATA-DGR:**

- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1993
- **Label** 3
- **Packaging group:** III
- **Proper shipping name:** FLAMMABLE LIQUID, N.O.S. (XYLENES, TOLUENE)

· **UN "Model Regulation":** UN1993, FLAMMABLE LIQUID, N.O.S., 3, III

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xn Harmful

· **Hazard-determining components of labelling:**

xylene

· **Risk phrases:**

- 10 Flammable.
- 20/21 Harmful by inhalation and in contact with skin.
- 38 Irritating to skin.

· **Safety phrases:**

- 2 Keep out of the reach of children.
- 36/37 Wear suitable protective clothing and gloves.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 56 Dispose of this material and its container to hazardous or special waste collection point.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 30.05.2010

Revision: 30.05.2010

Trade name: Under Coat Omega100

(Contd. of page 6)

· Relevant R-phrases

- 10 Flammable.
- 11 Highly flammable.
- 20/21 Harmful by inhalation and in contact with skin.
- 38 Irritating to skin.
- 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- 63 Possible risk of harm to the unborn child.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· Department issuing MSDS: Product safety department**· Contact: Mr. Rashad****· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

GB