



KAPCI
COATINGS

For professional use only

Issue date: July 2010

Superseded TDS: February 2009

26

Kapci 222 1K Undercoat

Product description

Kapci 222 is 1K undercoat based on a special resin composition, designed to protect car underbody, body floor and other metal parts from corrosion. Kapci 222 gives anticorrosion properties, excellent adhesion and chemical resistance.

Suitable substrates and preparations

Kapci 222 undercoat should be applied over rust free and degreased bare metal. For longer resistance to corrosion it is recommended applying any Kapci anticorrosive primer (Kapci 810/Kapci 850/Kapci 880) prior to undercoating with Kapci 222.





These products are for the professional painting of automotive vehicles only after reference to the manufacturer's Material Safety Data Sheets

www.kapci.com



Kapci Car
Refinishes
System

Product Process

Product	Kapci 222
Thinner	Kapci 525
	Bare metal should be degreased with Kapci 606 degreaser. Painted surfaces should be degreased with Kapci 605 degreaser.
	By weight: Add 20% Kapci 525 thinner;
	Use the special UB gun for underbody products. Nozzle: 4-5mm; Pressure:4-5 bar Apply in 1-2 coats.
	Air dry at 20°C Dust free: 40-50 min Touch dry: 3-5 h Hard dry: 24 h

Health and Safety

1. For full Health and Safety information please refer to Material Safety Data Sheet;
2. Observe the precautionary notices displayed on the container;
3. Goggles and suitable protective equipment must be worn while using these products;
4. Good ventilation must be provided in the working environment;