



KAPCI
COATINGS

Decorative Paints

www.kapci.com

03

Kapci Coat 733

Description

Kapci Coat 733 is a matt finish based on a modified acrylic emulsion for interior surfaces.

Technical Data

Viscosity	47±3ku
Solid content	62±3%
Density	1.62±0.03gm/cm ³
Gloss	Matt
Coverage	6-8 m ² /kg (Dry film thickness 45-50 μ)

Product Features

- Alkali resistant;
- Easy to apply;
- Good leveling;

Substrates and surface preparation

Kapci Coat 733 is recommended for interior application over bricks, plaster, concrete or cement sheets. All new or already painted surfaces should be free from dust, grease and waxes.

Application

New Surfaces

1. Apply Kapci Sealer 751 in one coat;
2. Apply Kapci Putty 750 in two cross layers;
3. Apply Kapci Coat 733 as a top coat in two coats after dilution with water (15 % dilution) to reach the suitable application viscosity.

Old surface painted with oil or alkyd paints

1. Sand and remove dust;
2. Apply Kapci Super Matt 766 in one coat;
3. Apply Kapci Coat 733 as a top coat in two coats after dilution with water (15 % dilution) to reach the application viscosity.

Decorative
Paints

Old painted surface with emulsion paints

1. Washing with water & liquid soap;
2. Rinse with water;
3. Apply Kapci Sealer 751 in one coat;
4. Apply Kapci Coat 733 as a top coat in two coats after dilution with water (15 % dilution) to reach the suitable application viscosity.

Drying time at 25 °C & 60% R.H

Initial drying time	1h
Recoating time	4h
Final drying time	6h

Tools

Brush, roller or airless spray gun
Cleaner: water

Color

White and can be colored

Expiry

Two years from production date if stored in original sealed container at normal temperature.
Keep away from direct sun light.