



**KAPCI**  
**COATINGS**

Decorative Paints

[www.kapci.com](http://www.kapci.com)

04

# Kapci Latico 737

## Description

Kapci Latico 737 is a matt finish based on a modified acrylic emulsion with good hiding and whiteness for interior surfaces.

## Technical Data

Viscosity	48±3ku
Solid content	62±3%
Density	1.62±0.03gm/cm <sup>3</sup>
Gloss	Matt
Coverage	6-9 m <sup>2</sup> /kg (Dry film thickness 45-50 μ)

## Product Features

- Alkali resistant;
- Easy to apply;
- Good leveling;
- Good whiteness;
- Good hiding power;

## Substrates and surface preparation

Kapci Latico 737 is recommended for application over bricks, plaster, concrete or cement surfaces. All new or already painted surfaces should be free from dust, grease and waxes.

## Application

### New Surfaces

1. Apply Kapci Sealer 751 in one coat;
2. Apply Kapci Putty 750 in two cross layers;
3. Apply Kapci Latico 737 in two coats after dilution with water (15 % dilution) to reach the application viscosity.

### Old painted surface with oil or alkyd paints

1. Sand and remove dust;
2. Apply Kapci Super Matt 766 in one coat;
3. Apply Kapci Latico 737 in two coats after dilution with water (15 % dilution) to reach the application viscosity.

Decorative  
Paints

## Old painted surface with emulsion paints

1. Washing with water & liquid soap;
2. Rinse with water;
3. Apply Kapci Sealer 751 in one coat;
4. Apply Kapci Latico 737 as a top coat in two coats after dilution with water (15 % dilution) to reach the suitable application viscosity.

## Drying time at 25 °C & 60% R.H

Initial drying time	1h
Recoating time	4h
Final drying time	6h

## Tools

Brush, roller or airless spray gun  
Cleaner: water

## Color

White and can be colored

## Expiry

Two years from production date if stored in original sealed container at normal temperature.  
Keep away from direct sun light.