



**KAPCI**  
**COATINGS**

Decorative Paints

09

[www.kapci.com](http://www.kapci.com)

# Kapci Clear 752

## Description

Kapci Clear 752 is water based transparent varnish based on modified acrylic emulsion recommended for interior and exterior application where high quality finish is required.

## Technical Data

Viscosity	18±3 ku
Solid content	26±3 %
Density	0.98 ±0.03gm/cm <sup>3</sup>
Gloss	High Gloss
Coverage	16-20 m <sup>2</sup> /kg (as ready for use products)

## Product Features

- Alkali resistant;
- Washable;
- Excellent non-yellowing properties;
- Flexible to accommodate hair cracks in substrate;

## Substrates and surface preparation

Kapci Clear 752 is recommended for application over matt emulsion paints, masonry, bricks, plaster, concrete and cements sheets. All new or previously painted surfaces should be free from dust, grease and waxes.

## Application

### New Surfaces

1. Apply Kapci Sealer 751 in one coat;
2. Apply Kapci Putty 750 in two cross layers;
3. Apply Kapci Sealer 751 in one coat again;
4. Apply suitable type of matt emulsion paint (Kapci Latico 737 or Kapci Coat 733) in two coats;
5. Apply Kapci Clear 752 in two coats after dilution with water (100 % dilution) to reach the suitable application viscosity.

Decorative  
Paints

### **Old surfaces previously painted with alkyd paints**

1. Sand and remove dust;
2. Apply Kapci Super Matt 766 in one coat;
3. Apply suitable type of matt emulsion paint (Kapci Latico 737 or Kapci Coat 733) in two coats;
4. Apply Kapci Clear 752 in two coats after dilution with water (100 % dilution) to reach the application viscosity.

### **Old surfaces previously painted with emulsion paints**

1. Wash with water & liquid soap;
2. Rinse with water;
3. Apply Kapci Sealer 751 in one coat;
4. Apply suitable type of matt emulsion paint (Kapci Latico 737 or Kapci Coat 733) in two coats;
5. Apply Kapci Clear 752 in two coats after dilution with water (100 % dilution) to reach the application viscosity.

### **Drying time at 25 °C & 60% R.H**

Initial drying time	1h
Recoating time	4h
Final drying time	6h

### **Tools**

Brush or roller  
Cleaner: water

### **Color**

Transparent

### **Expiry**

Two years from production date if stored in original sealed container at normal temperature.  
Keep away from direct sun light.