



KAPCI
COATINGS

Decorative Paints

www.kapci.com

10

Kapci Sealer 756

Description

Kapci Sealer 756 is water based acrylic sealer especially designed for application in exterior over concrete, plaster, bricks and stones. It is recommended for surfaces pretreatment.

Technical Data

Viscosity	18±3 ku
Solid content	50±3 %
Density	1.20±0.03gm/cm ³
Gloss	Matt
Coverage	16-20 m ² /kg (as ready for use products)

Product Features

- Good impregnating ability into cement;
- Fast drying;
- Easily applied;
- Chemical resistant to alkaline compounds;
- High coverage;
- Economic cost;

Substrates and surface preparation

Kapci Sealer 756 is recommended as a priming coat for cement and plaster in exterior, to consolidate the superficial layer of such surfaces. It is used as sealer to ensure excellent adhesion of subsequent water based coating system. All new or already painted surfaces should be free from dust, grease and waxes.

Application

1. Apply Kapci Sealer 756 in one coat after dilution with water (100 % dilution) to reach the application viscosity.
2. Apply Kapci Putty 749 or Kapci Putty 750 in two cross layers;

Drying time at 25 °C & 60% R.H

Initial drying time	1h
Final drying time	6h

Decorative
Paints

Tools

Brush or roller
Cleaner: water

Color

White (after drying)

Expiry

Two years from production date if stored in original sealed container at normal temperature.
Keep away from direct sun light.