



KAPCI
COATINGS

Decorative Paints

www.kapci.com

19

Kapci Crack Filler 790

Description

Kapci Crack Filler 790 is high quality putty based on acrylic copolymer especially developed for use in interior and exterior. It is used to refill cracks and holes on different kind of damaged surfaces.

Technical Data

Solid content	55±3 %
Density	0.42±0.03gm/cm ³
Coverage	Depending on size and kind of damage

Product Features

- No shrinkage;
- Very good bonding to plasters, wallboards or wooden surfaces.

Substrates and surface preparation

Kapci Crack Filler 790 can be used for plaster, wallboards or wood. All new or previously painted surfaces should be free from dust, grease and waxes.

Application

1. Stir well before use;
2. It is recommended to apply suitable primer, Kapci Sealer 751 or Kapci Sealer 756, prior to applying Kapci Crack Filler 790;
3. Enlarge damage (cracks, holes) by using putty knife. Clean them well by removing dust and loose fine and coarse particles;
4. Apply Kapci Crack Filler 790 to get even and smooth surface;
5. Allow drying for 12h and repaint.

Drying time at 25 °C & 60% R.H

Initial drying time	15 min
Final drying time	12h

Tools

Putty knife
Cleaner: water

Decorative
Paints

Color

White

Expiry

Two years from production date if stored in original sealed container at normal temperature.
Keep away from direct sun light.