



KAPCI
COATINGS

For professional use only

Issue date: February 2015
Superseded: February 2014

Kapci 003 Paint Remover

Product description

Kapci 003 is solvent-based paint remover designed for removal of paints (acrylic, polyurethane, and epoxy) from metal surfaces.

Kapci 003 paint remover is thixotropic, mildly alkaline chemical liquid that penetrates the paint and ensures its easy removal.

Do not use Kapci 003 for paint stripping over plastics, plastic tiles, linoleum or fibers.

This product is ready for use.

Application



Apply Kapci 003 in heavier coats by brush

or



apply heavier coats by roller



Leave for 30 min to paint swell

Paint removal: Remove the old paint by scraper or by putty knife. Repeat the procedure if needed.

These products are for the professional painting of automotive vehicles only after reference to the manufacturer's Material Safety Data Sheets (MSDS)

Rev (01) 02/2015



KAPCI
COATINGS

For professional use only

Issue date: February 2015
Superseded: February 2014

General notes

Other tips

1. Open the container slowly to release possible pressure build up.
2. Optimal storage of Kapci 003 paint remover is from 8°C-21°C.

Health and Safety

1. For full Health and Safety information, refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.

IMPORTANT NOTE: These products are for professional use only. The information in this Technical Data Sheet is based on our best knowledge and given for information purposes only without any obligation as we do not have control over the quality and conditions of the surface, or over many factors affecting the use and application of the product. Always read the Material Safety Data Sheet and the Technical Data Sheet for this product if available.