



KAPCI
COATINGS

For professional use only

Issue date: February 2015
Superseded: February 2014

Kapci 100S Underbody

Product description

Kapci 100S is a product based on cyclo rubber designed to protect car underbody from stone chipping and corrosion. It can also be applied over the body floor and other metal parts. Kapci 100S gives anticorrosion properties, excellent adhesion and chemical resistance. The product is ready for use.

Substrates

Kapci 100S undercoat should be applied over rust free and degreased bare metal. For longer resistance to corrosion, it is recommended to apply an anticorrosive primer prior to overcoating with Kapci 100S.

Application



Thoroughly degrease the surface. For steel use Kapci 606 degreaser for metal.



Kapci 100S is ready for use product. Shake the product well before use.



Use special underbody (UB) gun for underbody products.
Nozzle: 6-8mm; Pressure: 4-5 bar
Apply 1-2 coats.



Air dry at 20°C:
Dry to handle: 1-2h
Hard dry: 24h

These products are for the professional painting of automotive vehicles only after reference to the manufacturer's Material Safety Data Sheets (MSDS).

Rev (01) 02/2015



KAPCI
COATINGS

For professional use only

Issue date: February 2015
Superseded: February 2014

Health and Safety

1. For full Health and Safety information refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.

IMPORTANT NOTE: These products are for professional use only. The information in this Technical Data Sheet is based on our best knowledge and given for information purposes only without any obligation as we do not have control over the quality and conditions of the surface, or over many factors affecting the use and application of the product. Always read the Material Safety Data Sheet and the Technical Data Sheet for this product if available.

Rev (01) 02/2015