



KAPCI
COATINGS

Issue date: September 2017
Superseded: May 2017

Kapci 1200 Crackle Finish

Product properties

Kapci 1200 Crackle finish is a product which offers outstanding and homogeneous cracking finish effect. It is produced as both transparent and colored crackle finish. For better protection of the finish product, we recommend applying of Kapci nitrocellulose clearcoats over Kapci 1200.

Gloss: Matt

Theoretical coverage: 5-7 m²/kg per a coat

Products for application

Kapci 1200 Crackle Finish

Kapci 200/201/205 Nitrocellulose Paint

Kapci 525 Nitrocellulose thinner

Substrates and surface preparation

Kapci Crackle 1200 is recommended for application over both metal and wooden surfaces after properly primed and sanded surface.

Mixing ratio by weight

Kapci 1200 Crackle finish	100%
Kapci 525 Nitrocellulose thinner	30-50%

Application

Kapci nitrocellulose paints such as Kapci 200, Kapci 201 or Kapci 250 (refer to relevant product TDS) should be applied prior to spraying of Kapci 1200 Crackle Finish.

For better surface protection, it is recommend to apply Kapci NC clearcoat (refer to the product TDS) over Kapci 1200 Crackle Finish.

Drying time at 25°C

Dry tack free: 20-30 min

Through dry: approx. 1h

Rev (03) 09/2017



KAPCI
COATINGS

Issue date: September 2017
Superseded: May 2017

Other tips

1. Kapci 1200 Crackle finish can be overcoated after minimum 1 hour/25 °C.
2. Practical coverage depends on several factors including shape, roughness and porosity of the object to be painted, spraying equipment used, application methods, application conditions, film thickness, etc.
3. For best results, it is always recommended to test the products on scrap pieces of wood before start paint job.

Shelf life

3 years from production date, stored in original packaging at normal conditions.

Health and Safety

1. For full Health and Safety information refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Good ventilation must be provided in the working environment.

IMPORTANT NOTE: The information in this Technical Data Sheet is based on our best knowledge and given for information purposes only without any obligation as we do not have control over the quality and conditions of the surface, or over many factors affecting the use and application of the product. Always read the Material Safety Data Sheet and the Technical Data Sheet for this product if available.

Rev (03) 09/2017