



KAPCI
COATINGS

Issue date: May 2017

Turbo 6200 Fast drying clearcoat for inner surfaces

Product properties

Turbo 6200 is a synthetic, fast drying clearcoat especially designed for the inner surface of furniture.

Theoretical coverage, m²/kg 4-6 per a coat

Products for application

Turbo 6200
KAPCI 555 Thinner or White Spirit Thinner

Substrate and surface preparation

Turbo 6200 is suitable for application over any kind of wooden surfaces previously treated with nitrocellulose (NC) sealer. Before overcoating with Turbo 6200, the surface should be sanded with P320 or P400 sanding paper.

Mixing ratio by weight

	By spraying	By brush
Turbo 6200 Fast Drying Clearcoat	100 %	100 %
KAPCI 555 Thinner or White Spirit Thinner	30-35 %	20-25 %

Application

Turbo 6200 is applied in 2 coats by spraying or by brush.
Spray gun tips: Nozzle 1.3 mm; Pressure 2 Bar (HVLP); 3.0-3.5 bar (Conventional)

Drying time at 25°C

Dry to touch: 30 min
Hard dry: 4 h

Other tips

Practical coverage depends on several factors including shape, roughness and porosity of the object to be painted, spraying equipment used, application methods, application conditions, film thickness, etc.

Rev (01) 05/2017



KAPCI
COATINGS

Issue date: May 2017

Shelf life

1 year from production date stored in original packaging at normal conditions.

Health and Safety

1. For full Health and Safety information please refer to the Material Safety Data Sheet.
2. Observe the precautionary notices displayed on the container.
3. Good ventilation must be provided in the working environment.

IMPORTANT NOTE: The information in this technical data sheet is based on our best knowledge and given for information purposes only without any obligation as we do not have control over the quality and conditions of the surface, or over many factors affecting the use and the application of the product. Always read the Materials Safety Data Sheet and the Technical Data Sheet for this product if available.

Rev (01) 05/2017