



KAPCI
COATINGS

Wood Coatings

www.kapci.com

07

Kapci 2000 NC Sealer HV

1- Product properties

Kapci 2000 HV is a high viscosity transparent nitrocellulose sealer with excellent filling and sanding properties. It gives good coverage, leveling and adhesion on different types of wood.

Viscosity	72 ± 2 Pas at 25°C
Density	42 ± 2%
Solid Content	1.00 ± 0.02 g/cm ³
Coverage	6 – 8 m ² /kg

2- Products for application

Kapci 2000 NC Sealer HV
Kapci 525 NC Thinner

3- Suitable substrate and surface preparation

Kapci 2000 HV is suitable for application over almost any type of wood.

4- Method of application

By spray or by curtain coater, thinned 300% with Kapci 525 thinner to reach correct application viscosity. It can be applied also by brush.

The product can be applied more than in one coat. Flash off time between coats is 10 minutes. Maximum quantity to apply this product is 150 g/m².

It may be overcoated with Kapci matt and Kapci Gloss topcoats, either clear or pigmented ones.

5- Drying at 25°C

Dust Free	30 min
Complete dry	2-4 hrs
Sanding	2-4 hrs

6- Color

Transparent dark / Transparent light.

7- Expiry

3 years from production date in original container at normal temperature.

8- Material safety data

When use these products it is required to comply with the national regulations for health and safety.

Wood
Coatings