



KAPCI
COATINGS

Wood Coatings

www.kapci.com

11

Kapci 2002 Synthetic Varnish

1- Product properties

Kapci 2002 is an alkyd clearcoat that gives high gloss, high resistance against water and chemicals. It is suitable for clearcoating over wood, windows, doors and boats. Kapci 2002 can also be used for applying over walls.

Viscosity	33 ± 2 sec / Ford cup 6 at 25°C
Density	0.92 – 0.94 g/cm ³
Solid Content	40 ± 2 %
Coverage	11 – 14 m ² /kg
Gloss	High Gloss

2- Products for application

Kapci 2002 Synthetic Varnish
Kapci 555 Thinner

3- Suitable substrate and surface preparation

For wooden windows, wood works, boats, kitchens etc. It can be applied on both wood and walls, after proper priming. Surface must be dry, smooth and clean from dust, oils and greases. Priming may be required in some cases.

4- Method of application

Apply by spray gun or brush, thinned with Kapci 555 up to maximum 30% to reach correct application viscosity.

5- Drying at 25°C

Dry to touch	2-3 hrs
Hard dry	24 hrs

6- Expiry

3 years from production date in original container at 20°C.

7- Material safety data

When use these products it is required to comply with the national regulations for health and safety.

Wood
Coatings