



KAPCI
COATINGS

Wood Coatings

www.kapci.com

25

Kapci 2800 Wood Stain

1- Product properties

Kapci 2800 is a highly concentrated solvent based wood stain. It is specially designed for coloring of wooden surfaces before applying Nitrocellulose, Polyester and Polyurethane finishes. Kapci 2800 gives good light fastness and fast drying.

Viscosity	11± 2 sec / Ford cup 4 at 25°C
Density	0.86 ± 0.02 g/cm ³
Solid Content	7 ± 2%
Coverage	8 - 10 m ² /kg

2- Products for application

- Kapci 2800 Wood Stain
- Kapci 525 Nitrocellulose thinner
- Water
- Alcohol

NOTE: - In case that water is diluent, water will prolong drying time and cause rising of wood fibers.
- Kapci 2800 should be shaken well before use.

3- Suitable substrate and surface preparation

Suitable for application on almost any type of wood previously properly sanded.

4- Mixing ratio

Kapci 2800	1 part
Kapci 525/ or water/ or alcohol	9 parts

5- Method of application

Kapci 2800 is applied by spraying, brush, roller or cotton.

6- Drying at 25°C

Dust free	20 min
Complete dry	1 h

7- Color

According to Kapci color chart

8- Expiry

3 years from production date in original container at 20°C.

Wood
Coatings